



链号 Chain No.	节距 Pitch	滚子 直径 Roller diameter	内节 内宽 Width between inner	销轴 直径 Pin diameter	销轴 长度 Width over bearing	连接销 轴长度 Width over connecting	内链板 高度 Inner plates depth	排距 Transverse pitch	链板 厚度 Plate thickness	抗拉 强度 Ultimate tensile strength	平均抗 拉强度 Average tensile strength	每米 重量 Mass per meter
GB ISO ANSI	p	d1 max	plates b1 min	d2 max	pins L max	pins Lc max	h2 max	pt	T	Fu min	Fua	q ≈
	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN	kN	kg/m
60H	19.05	11.91	12.57	5.96	30.2	34.8	18.10	—	3.18	31.3	40.6	1.87
60H-2	19.05	11.91	12.57	5.96	56.3	60.9	18.10	26.11	3.18	62.6	80.3	3.71
60H-3	19.05	11.91	12.57	5.96	82.4	87.0	18.10	26.11	3.18	93.9	108.2	5.54
80H	25.40	15.88	15.75	7.94	37.4	42.8	24.13	—	3.96	55.6	67.8	3.10
80H-2	25.40	15.88	15.75	7.94	70.0	75.4	24.13	32.59	3.96	111.2	138.0	6.15
80H-3	25.40	15.88	15.75	7.94	102.6	108.0	24.13	32.59	3.96	166.8	193.0	9.42
100H	31.75	19.05	18.90	9.54	44.5	50.6	30.17	—	4.75	87.0	106.8	4.52
100H-2	31.75	19.05	18.90	9.54	83.6	89.7	30.17	39.09	4.75	174.0	214.0	9.03
100H-3	31.75	19.05	18.90	9.54	122.7	128.8	30.17	39.09	4.75	261.0	299.0	12.96
120H	38.10	22.23	25.22	11.11	55.0	61.6	36.20	—	5.56	125.0	153.0	6.60
120H-2	38.10	22.23	25.22	11.11	103.9	110.5	36.20	48.87	5.56	250.0	306.0	13.13
120H-3	38.10	22.23	25.22	11.11	152.8	159.4	36.20	48.87	5.56	375.0	422.0	19.64
140H	44.45	25.40	25.22	12.71	59.0	66.4	42.23	—	6.35	170.0	206.0	8.30
140H-2	44.45	25.40	25.22	12.71	111.2	118.6	42.23	52.20	6.35	340.0	416.0	16.60
140H-3	44.45	25.40	25.22	12.71	163.4	170.8	42.23	52.20	6.35	510.0	568.0	24.90
160H	50.80	28.58	31.55	14.29	69.4	77.3	48.26	—	7.14	223.0	272.0	11.20
160H-2	50.80	28.58	31.55	14.29	131.3	139.2	48.26	61.90	7.14	446.0	543.0	22.30
160H-3	50.80	28.58	31.55	14.29	193.2	201.1	48.26	61.90	7.14	669.0	748.0	33.50
180H	57.15	35.71	35.48	17.46	77.3	86.4	54.30	—	7.92	281.0	325.0	14.83
180H-2	57.15	35.71	35.48	17.46	146.5	155.6	54.30	69.16	7.92	562.0	643.0	29.60
180H-3	57.15	35.71	35.48	17.46	215.7	224.7	54.30	69.16	7.92	843.0	890.0	44.40
200H	63.50	39.68	37.85	19.85	87.1	97.3	60.33	—	9.52	347.0	422.0	19.16
200H-2	63.50	39.68	37.85	19.85	165.4	175.6	60.33	78.31	9.52	694.0	850.0	38.30
200H-3	63.50	39.68	37.85	19.85	243.7	253.9	60.33	78.31	9.52	1041.0	1167.0	57.46
240H	76.20	47.63	47.35	23.81	111.4	121.9	72.39	—	12.70	500.0	591.0	30.40
240H-2	76.20	47.63	47.35	23.81	212.6	223.1	72.39	101.22	12.70	1000.0	1167.0	60.80
240H-3	76.20	47.63	47.35	23.81	313.8	324.3	72.39	101.22	12.70	1500.0	1620.0	91.10