



链号 Chain No.		节距 Pitch	滚子 直径 Roller diameter	内节 内宽 Width between inner	销轴 直径 Pin diameter	内链板 高度 Inner plates depth	销轴 长度 Width over bearing	连接销 轴长度 Width over connecting	链板 厚度 Plate thickness	抗拉 强度 Ultimate tensile strength	动载 载荷 Dynamic strength	每米 重量 Mass per meter
ISO JCAS	Dong feng	p	d1 max	plates b1 min	d2 max	h2 max	pins L max	pins Lc max	t/T	Fu min	Fud min	q ≈
		mm	mm	mm	mm	mm	mm	mm	mm	kN	N	kg/m
*25H	*25H	6.350	3.30	3.10	2.31	6.00	9.1	10.1	1.00	4.80	810	0.17
*219H	*219H	7.774	4.59	4.68	3.17	7.60	12.6	14.3	1.40	7.30	1260	0.28
420	420	12.70	7.77	6.25	3.99	12.00	14.9	16.4	1.50	15.60	2860	0.55
420H	420H	12.70	7.77	6.25	3.99	12.00	17.5	18.9	1.80	20.00	3420	0.76
428	428	12.70	8.51	7.85	4.51	12.00	16.9	18.8	1.50	15.70	2860	0.69
428H	428H	12.70	8.51	7.85	4.51	12.00	18.9	20.8	2.00	20.50	3420	0.79
520	520	15.875	10.16	6.25	5.09	15.30	17.5	19.7	2.00	26.40	4840	0.89
520H	520H	15.875	10.16	6.25	5.09	15.30	19.0	21.2	2.20	31.30	5170	1.10
530	530	15.875	10.16	9.40	5.09	15.30	20.8	22.9	2.00	26.40	4840	1.06
530SH	530SH	15.875	10.22	9.40	5.40	15.30	23.1	25.1	2.40	30.40	5490	1.24
630	630	19.05	11.91	9.40	5.96	18.60	24.0	26.2	2.40	35.30	7290	1.50
	520R	15.875	10.16	7.00	5.09	13.50	18.2	20.5	1.9/1.75	22.50	4240	0.78

\*套筒链：表中滚子直径d1为套筒直径。

\*Bushing chain: d1 in the table indicates the external diameter of the bushing.