



| 链号 Chain No. | 节距 Pitch | 滚子 直径 Roller diameter | 内节 内宽 Width between inner | 销轴 直径 Pin diameter | 销轴 长度 Width over bearing | 连接销 轴长度 Width over connecting | 内链板 高度 Inner plates depth | 排距 Transverse pitch | 链板 厚度 Plate thickness | 每米 重量 Mass per meter |
|-----------------|-------------|--------------------------------|---------------------------------------|-----------------------------|--------------------------------------|---|---------------------------------------|---------------------------|--------------------------------|----------------------------------|
| Dongfeng | p | d1 max | b1 min | d2 max | L max | Lc max | h2 max | pt | t/T max | q ≈ |
| | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg/m |
| *25ZP | 6.35 | 3.30 | 3.10 | 2.31 | 9.10 | 11.60 | 6.02 | 6.40 | 0.76 | 0.15 |
| *35ZP | 9.525 | 5.08 | 4.68 | 3.60 | 13.20 | 16.50 | 9.05 | 10.13 | 1.27 | 0.33 |
| 40ZP | 12.70 | 7.92 | 7.85 | 3.98 | 17.80 | 21.70 | 12.07 | 14.38 | 1.52 | 0.62 |
| 50ZP | 15.875 | 10.16 | 9.40 | 5.09 | 21.80 | 25.90 | 15.09 | 18.11 | 2.03 | 1.02 |
| 60ZP | 19.05 | 11.91 | 12.57 | 5.96 | 26.90 | 31.50 | 18.10 | 22.78 | 2.39 | 1.50 |
| 80ZP | 25.40 | 15.88 | 15.75 | 7.94 | 33.50 | 38.90 | 24.13 | 29.29 | 3.18 | 2.60 |
| 100ZP | 31.75 | 19.05 | 18.90 | 9.54 | 41.10 | 47.20 | 30.17 | 35.76 | 3.96 | 3.91 |
| 120ZP | 38.10 | 22.23 | 25.22 | 11.11 | 50.80 | 57.40 | 36.20 | 45.44 | 4.75 | 5.62 |
| 140ZP | 44.45 | 25.40 | 25.22 | 12.71 | 54.90 | 62.30 | 42.23 | 48.87 | 5.56 | 7.50 |
| 160ZP | 50.80 | 28.58 | 31.55 | 14.29 | 65.50 | 73.40 | 48.26 | 58.55 | 6.35 | 10.10 |
| 180ZP | 57.15 | 35.71 | 35.48 | 17.46 | 73.90 | 83.00 | 54.30 | 65.84 | 7.14 | 13.95 |
| 05BZP | 8.00 | 5.00 | 3.00 | 2.31 | 8.60 | 11.70 | 11.70 | 7.10 | 0.80 | 0.20 |
| #06BZP | 9.525 | 6.35 | 5.72 | 3.28 | 13.50 | 16.80 | 16.80 | 8.26 | 1.30 | 0.41 |
| 08BZP | 12.70 | 8.51 | 7.75 | 4.45 | 17.00 | 20.90 | 20.90 | 11.80 | 1.60 | 0.69 |
| 10BZP | 15.875 | 10.16 | 9.65 | 5.08 | 19.60 | 23.70 | 23.70 | 14.60 | 1.70 | 0.93 |
| 12BZP | 19.05 | 12.07 | 11.68 | 5.72 | 22.70 | 27.30 | 27.30 | 16.10 | 1.85 | 1.15 |
| 16BZP | 25.40 | 15.88 | 17.02 | 8.28 | 36.10 | 41.50 | 41.50 | 21.00 | 4.15/3.1 | 2.71 |
| 20BZP | 31.75 | 19.05 | 19.56 | 10.19 | 43.20 | 49.30 | 49.30 | 26.40 | 4.5/3.5 | 3.70 |
| 24BZP | 38.10 | 25.40 | 25.40 | 14.63 | 53.40 | 60.00 | 60.00 | 33.40 | 6.0/4.8 | 7.10 |
| 28BZP | 44.45 | 27.94 | 30.99 | 15.90 | 65.10 | 72.50 | 72.50 | 37.00 | 7.5/6.0 | 8.50 |
| 32BZP | 50.80 | 29.21 | 30.99 | 17.81 | 67.40 | 75.30 | 75.30 | 42.20 | 7.0/6.0 | 10.25 |

*套筒链：表中滚子直径d₁为套筒直径。

*Bushing chain: d₁ in the table indicates the external diameter of the bushing.

直板链 Straight side plates

注意：其它的A、B系列双排链和双节距链，也可按需镀锌。

Note: Other kinds of A、B series doubling Chains and double pitch chains may also be available upon require.